



A GUIDE TO FITTING VINYL GRAPHICS

Step 1

Align Graphic
Align Graphic & Fix in Desired Position with Masking Tape

When you have received your decal it is best to ensure that the graphic is firmly pressed down onto the application paper making sure that there are no air bubbles present, this can affect the application. Every effort is taken in our cutting department to ensure decals are in a pristine condition prior to delivery, sometimes due to atmospheric conditions, the decal can lift from the application tape. A few moments spent now can save minutes and money later.

Step 2

Align Graphic
Cut Between Lettering & Logos Where Possible on Large Graphics for Easier Fitting

Wash the surface that you wish to apply the decal to with a weak solution of washing up liquid and warm water. Please note that the surface must be clean of any wax, oil or greasy residues before applying. Depending on the surface to which the decal is to be applied, it may be advisable to wipe the surface with methylated spirit or similar cleaner first.

IMPORTANT - Please test the spirit on a concealed area of the surface to ensure no adverse reaction takes place.

Continued on next page . . .

Step 3

Align Graphic Carefully Making Sure it is Aligned to any Other Graphic or Surface Feature Near by
Peel Away the Backing Paper Carefully and then with a Gentle Tug - Remove It

You may need help aligning the graphic to ensure it is perfectly straight, a good tip is to mark out where you want your graphics to be placed with masking tape and use it as a guideline, this careful preparation and planning makes all the difference. On very large scale graphics, tape over one end of the graphic whilst the backing and application paper is still in place using masking tape to ensure it remains where you want it on your vehicle. Now with the help of a friend or partner, lift up the untaped end and remove the backing carefully until you are able to pull it free from the taped end of the application paper. Have a friend or partner hold the untaped end of the application paper whilst you lay the graphic down, smoothing it onto your surface from the taped end gradually a bit at a time. In very cold weather it may be helpful to gently warm the area you are working on using a hair drier or similar appliance.

IMPORTANT - Care should be taken when using electrical appliances near water or in the open.

These fitting instructions and website wording are the copyright of Fizzsigns.com and it's owners.

© Fizzsigns.com 2007

Fizzsigns.com